

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 02111 Tape-Ex -300 ml-
- · Article number: P7000022, 75 0664
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture: Instrument cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Key Surgical GmbH Zum Windpark 1

Zum Windpark 1 23738 Lensahn

Tel: +49.4363.90590.0 Fax: +49.4363.90590.590 Mail: info@keysurgical.de Website: www.keysurgical.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: During normal opening times: +49 4363 905900

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



### GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.	Skin Irrit. 2	H315	Causes skin irritation.
	Skin Sens. 1	H317	May cause an allergic skin reaction.
	STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.	Asp Tox 1	H304	May be fatal if swallowed and enters airways

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS09

(Contd. of page 1)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

· Signal word Danger

### Hazard-determining components of labelling:

pentane

(R)-p-mentha-1,8-diene

Hydrocarbons, C6, isoalkanes, <5% n-hexane

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

*P273* Avoid release to the environment.

P280 Wear protective gloves.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EINECS: 203-692-4	pentane	30-50%
Index number: 649-328-00-1	Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	30-50%
I L	butane, pure Flam. Gas 1, H220	10-20%
EINECS: 227-813-5	(R)-p-mentha-1,8-diene Flam. Liq. 3, H226; Sap. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	1-10%

(Contd. on page 3)

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

G 10 - 1 00 1		(Contd. of pa
CAS: 74-98-6	propane	1-10
EINECS: 200-827-9	<b>◈</b> Flam. Gas 1, H220	
Index number: 601-003-00-5		
Reg.nr.: 01-2119486944-21-xxxx		
CAS: 75-28-5	isobutane	1-10
EINECS: 200-857-2	🚸 Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Index number: 601-004-00-0		
Reg.nr.: 01-2119485395-27-xxxx		
Regulation (EC) No 648/2004 on	detergents / Labelling for contents	
aliphatic hydrocarbons		≥30
perfumes (d-Limonene)		

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

(Contd. of page 3)

## · Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

### · Ingredients with limit values that require monitoring at the workplace:

#### 109-66-0 pentane

IOELV Long-term value: 3000 mg/m³, 1000 ppm

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

(Contd. of page 4)

### · Penetration time of glove material

*Value for the permeation: Level*  $\leq 6$ 

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye protection: Not required.

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on	hasic	nhysical	and	chemical	nronerties
7.1 Inivimunon on	vusic	pnysicui	unu	cnemicui	properties

· General Information

· Appearance:

Form: Aerosol
Colour: Colourless
Odour: Oranges
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: -60 °C

· Flammability (solid, gas): Not applicable.

• Ignition temperature: 255 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 0.7 Vol %

 Upper:
 10.9 Vol %

· Vapour pressure at 20 °C: 1,800 hPa

Density at 20 °C: 0.63 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic:Not determined.Kinematic:Not determined.

· Solvent content:

 Organic solvents:
 100.0 %

 VOC (EC)
 100.00 %

• 9.2 Other information No further relevant information available.

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

(Contd. of page 5)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
109-66-0 р	109-66-0 pentane		
Oral	LD50	>5,000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	
5989-27-5	5989-27-5 (R)-p-mentha-1,8-diene		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rabbit)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

### 5989-27-5 (R)-p-mentha-1,8-diene

EC50/48h | 0.36 mg/l (Daphnia magna (Großer Wasserfloh))

LC50/96h 0.72 mg/l (Pimephales promelas)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	1	O	O	U	1	0 7
· European	waste cata	logue				
15 01 10*	packaging	containing residues of	for co	ontamina	ted by hazardous sub	ostances
15 01 04	metallic p	ackaging				

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
IMDG	AEROSOLS (Naphtha (petroleum), hydrotreated ligh
IATA	PENTANES), MARINE POLLUTANT AEROSOLS, flammable
	AEROSOLS, Jiammaole
14.3 Transport hazard class(es)	
ADR	
¥2>	
Class	2 5F Gases.
Label	2.1
IMDG	
<b>1 1 1 1 1 1 1 1 1 1</b>	
Class	2.1
Label	2.1
IATA	
Class	2.1
Label	2.1

(Contd. on page 8)

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

	(Contd. of page
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substance
	(R)-p-mentha-1,8-diene, pentane
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat.
-	SW22 For AEROSOLS with a maximum capacity of 1 litr
	Category A. For AEROSOLS with a capacity above 1 litr
	Category B. For WASTE AEROSOLS: Category C, Cle
	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litro
0 0	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II o	of .
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
(= <u>£</u> )	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALI

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 25.03.2020 Version number 8 Revision: 25.03.2020

Trade name: 02111 Tape-Ex -300 ml-

(Contd. of page 8)

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: Product safety department

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 1: Flammable liquids - Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category I

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.